

SKY 120+

120mm CONSTRUCTION
DEPTH

Maximum size	15000 x 4950 mm				
Mounting type	Surface-mounted, recessed, ceiling, wall, Pendant				
Shape	Rectangular / square, round / oval, customised shape				
Profile surface standard	black, white, silver anodised				
Profile surface upgrades	RAL coating, special coating, Film special surface				
Luminous flux	1000 - 15000 lm/m²				
Colour temperature	2700 / 3000 / 4000 / 6000, TW 2700 - 6000, Dimt Warm 1800 - 3000, RGB / RGBW / RGBTW				
Colour rendering index	CRI +90, +95, +98				
Light distribution	Lambertsch				
Control system	On / Off, Dali / DMX / KNX, Casambi App, Dynamic				
Sound absorption	up to 0.85				
Accessories	Cable suspension, threaded rods (wall / ceiling mounting), customised construction				
Power supply unit	Built-in, externally or prepared on transformer plate				
Upgrades	Dust control layer (second, special textile banner inside)				
Light Upgrades	Edge illumination, electricity rail, spot set up, spot integrated, emergency light, sprinkler				
Textile banner Upgrades	Printing, acoustics, antibacterial, Fire protection B1 / B2				
Acoustics Upgrades	Acoustic foam rear wall, Acoustic textile banner				

