

SKY 150+

150mm CONSTRUCTION
DEPTH

Maximum size	20000 x 4950 mm			
Mounting type	Surface-mounted, recessed, ceiling, wall, Pendant			
Shape	Rectangular / square, round / oval, customised shape			
Profile surface standard	black, white, silver anodised			
Profile surface upgrades	RAL coating, special coating, Film special surface			
Luminous flux	1000 - 15000 lm/m²			
Colour temperature	2700 / 3000 / 4000 / 6000, TW 2700 - 6000, Dimt Warm 1800 - 3000, RGB / RGBW / RGBTW			
Colour rendering index	CRI +90, +95, +98			
Light distribution	Lambertsch			
Control system	On / Off, Dali / DMX / KNX, Casambi App, Dynamic			
Sound absorption	up to 0.85			
Accessories	Cable suspension, threaded rods (wall / ceiling mounting), customised construction			
Power supply unit	Built-in, external, prepared on transformer plate, on the rear (suspended luminous ceiling)			
Upgrades	Dust control layer (second, special textile banner inside)			
Light Upgrades	Edge illumination, electricity rail, spot set up, spot integrated, emergency light, sprinkler			
Textile banner Upgrades	Printing, acoustics, antibacterial, Fire protection B1 / B2			
Acoustics Upgrades	Acoustic foam rear wall, Acoustic textile banner			

