

SKY 150 OUTDOOR

150mm CONSTRUCTION
DEPTH

Maximum size	20000 x 4900 mm	
Mounting type	Surface-mounted, recessed, ceiling, wall, Pendant	
Shape	Rectangular / square, round / oval, customised shape	
Profile surface standard	black, white, silver anodised	
Profile surface upgrades	RAL coating, special coating, Film special surface	
Luminous flux	1000 - 15000 lm/m²	
Colour temperature	2700 / 3000 / 4000 / 6000, TW 2700 - 6000, Dimt Warm 1800 - 3000, RGB / RGBW / RGBTW	
Colour rendering index	CRI +90, +95, +98	
Light distribution	Lambertsch	
Control system	On / Off, Dali / DMX / KNX, Casambi App, Dynamic	
Sound absorption	up to 0.85	
Accessories	Cable suspension, threaded rods (wall / ceiling mounting), customised construction	
Power supply unit	Built-in, externally or prepared on transformer plate	
Upgrades	Dust control layer (second, special textile banner inside)	
Light Upgrades	Edge illumination, electricity rail, spot set up, spot integrated, emergency light, sprinkler	
Textile banner Upgrades	Printing, acoustics, antibacterial, Fire protection B1 / B2	
Acoustics Upgrades	Acoustic foam rear wall, Acoustic textile banner	

